





Economy Twin Switch Socket 13Amp

## Features & Benefits

- BSEN 1363 AC only contact gap 3mm
- Large capacity for easy terminal installation
- Supplied with M3.5 x 30mm Fixing Screws
- Fireproof moulded classic design
- Terminals accept up to 4 x 2.5mmÃ,² cables
- Dual Earth terminals for high integrity earthing
- Supplied with M3.5 x 30mm Fixing Screws



IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

## **Technical Specifications**

'	
General Information	
Colour/Finish	White
Dimensions (mm)	86 x 146 x 9mm
Front Plate Depth (mm)	9mm
Fixing Centre (mm)	120.6mm
Minimum Box Depth (mm)	Plastic / PVC Box - 25mm
Electrical	
Rated Operating Voltage (v)	240v
Terminal Capacity (mm²)	4 x 2.5mm <sup>2</sup>
Number Earth Terminals	2 Earth Terminals
Rated Load Capacity (Amps)	13A
Frequency (Hz)	50/60Hz
Number Poles	Single Pole
Approvals/Certifications	BS 1363 pt2
Kite Mark / ASTA	KM73109
Performance Data	
Outlets (1 / 2) etc	2 Gang
Switch (1 / 2) etc	2 Switches
Control (1 / 2 Way)	2 Ways
Lugs	N
Knockouts	N
Construction	
Body Material	Urea-Formaldehyde
Insert Colour	White insert
Weight (g)	190g
Warranty Period (Years)	25
Other	
Applications	Domestic, commercial applications



Email. info@cedelectrical.co.uk - Website. http://www.cedelectrical.co.uk