

## Model. CEDSSK2

2 Gang Switched Socket 13Amp

### Features & Benefits

- Economy - BSEN1363 (AC only) Contact Gap - 3mm
- Large capacity for easy terminal installation
- Fireproof moulded classic design
- Minimum Depth - Plastic/PVC Box - 25mm
- Terminal Capacity - 4 x 2.5mm<sup>2</sup> (13A only)
- Dual Earth terminals for high integrity earthing
- Supplied with M3.5 x 30mm fixing screws
- Flat Plate Depth - 13mm

### Safety Information

**IMPORTANT** - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

### Technical Specifications

| General Information                  |                                      |
|--------------------------------------|--------------------------------------|
| Colour/Finish                        | White                                |
| Dimensions (mm)                      | 86 x 146 x 9mm                       |
| Front Plate Depth (mm)               | 9mm                                  |
| Fixing Centre (mm)                   | 120.6mm                              |
| Minimum Box Depth (mm)               | Plastic / PVC Box - 25mm             |
| Electrical                           |                                      |
| Rated Operating Voltage (v)          | 240v                                 |
| Terminal Capacity (mm <sup>2</sup> ) | 4 x 2.5mm <sup>2</sup>               |
| Number Earth Terminals               | 2 Earth Terminals                    |
| Rated Load Capacity (Amps)           | 13A                                  |
| Frequency (Hz)                       | 50/60Hz                              |
| Number Poles                         | Single Pole                          |
| Approvals/Certifications             | BS 1363 pt 2                         |
| Kite Mark / ASTA                     | KM73109                              |
| Performance Data                     |                                      |
| Outlets (1 / 2) etc                  | 2 Gang                               |
| Switch (1 / 2) etc                   | 2 Switches                           |
| Control (1 / 2 Way)                  | 2 Ways                               |
| Lugs                                 | N                                    |
| Knockouts                            | N                                    |
| Construction                         |                                      |
| Body Material                        | Urea-formaldehyde                    |
| Insert Colour                        | White insert                         |
| Weight (g)                           | 200g                                 |
| Warranty Period (Years)              | 25                                   |
| Other                                |                                      |
| Applications                         | Domestic and commercial applications |

