

Model. CEDPS6T2

Pendant Set 6" Drop T2 100W to BS60598-2-1

Features & Benefits

- Available in - 6" & 9" length
- Clear Poly-carbonate Base
- Heat resistant cable 0.75mm² 2 core BASEC approved - BS 6141
- T2 - lamp holder (LHT2S) and ceiling rose (CR3TE)
- Energy Saving version for PL & PLC lamps (universal)
- BS EN-60598-2-1

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Colour/Finish	White
Dimensions (mm)	Ø88 x 256mm
Electrical	
Rated Operating Voltage (v)	250v
Terminal Capacity (mm ²)	2 x 1.5mm ²
Number Earth Terminals	1
Rated Load Capacity (Amps)	2A
Frequency (Hz)	50/60Hz
Approvals/Certifications	ASTA
Kite Mark / ASTA	lic. 917
Performance Data	
Construction	
Body Material	Urea Formaldehyde
Weight (g)	126g
Warranty Period (Years)	25
Other	
Applications	Domestic, commercial applications