





Model. AXMS32

10A Switch 3 Gang / 2 Way - ASTA

Features & Benefits

- 10Amp (X rated) suitable for inductive load
- Supplied with M3.5 x 25mm fixing screws
- Minimum Depth Metal/Plastic/PVC Box 16mm
- Terminal Capacity 3x1.5mmÃ,Â²
- Three Pole Isolators provide isolation of fans for maintenance or repair without isolation of complete circuit

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
 Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Colour/Finish	White
Dimensions (mm)	86 x 86 x 9mm
Front Plate Depth (mm)	9mm
Fixing Centre (mm)	60.3mm
Minimum Box Depth (mm)	16mm
Electrical	
Rated Operating Voltage (v)	240v
Terminal Capacity (mm ²)	3 x 1.5mmÃ,²
Rated Load Capacity (Amps)	10A
Frequency (Hz)	50/60Hz
Kite Mark / ASTA	ASTA
Performance Data	
Switch (1 / 2) etc	3 Gang
Control (1 / 2 Way)	2 Way
Construction	
Body Material	Urea Formaldehyde
Weight (g)	100.9g
Warranty Period (Years)	25
Other	

