



## Model. AXMSSK2

2 Gang Switched Socket 13A - ASTA

## Features & Benefits

- · Contact Gap 3mm
- Minimum Depth Plastic/PVC box 25mm
- Terminal Capacity 3 x 2.5mmÃ,Â<sup>2</sup> (13Amp only)
- Single Pole
- Supplied with M3.5 x 30mm fixing screws
- Front Plate Depth Single Pole 9mm

## Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
  Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

## **Technical Specifications**

| General Information                  |                   |
|--------------------------------------|-------------------|
| Colour/Finish                        | White             |
| Dimensions (mm)                      | 86 x 146 x 9mm    |
| Front Plate Depth (mm)               | 9mm               |
| Fixing Centre (mm)                   | 120.6mm           |
| Minimum Box Depth (mm)               | 25mm              |
| Electrical                           |                   |
| Rated Operating Voltage (v)          | 250v              |
| Terminal Capacity (mm <sup>2</sup> ) | 3 x 2.5mmÃ,²      |
| Number Earth Terminals               | 1 (single)        |
| Rated Load Capacity (Amps)           | 13A               |
| Frequency (Hz)                       | 50/60Hz           |
| Number Poles                         | 1 (Single)        |
| Kite Mark / ASTA                     | ASTA (lic. 913)   |
| Performance Data                     |                   |
| Outlets (1 / 2) etc                  | 2 Gang            |
| Switch (1 / 2) etc                   | 2 Switch          |
| Construction                         |                   |
| Body Material                        | Urea Formaldehyde |
| Weight (g)                           | 156g              |
| Warranty Period (Years)              | 25                |
| Other                                |                   |



