



Model. AXMSSK2DP

2 Gang Switched Socket 13A DP - ASTA

Features & Benefits

- Contact Gap 3mm
- Minimum Depth Plastic/PVC box 25mm
- Terminal Capacity 3 x 2.5mmÃ,Â² (13Amp only)
- 2 Earth Terminals for easy installation Single Pole
- Supplied with M3.5 x 30mm fixing screws
- Front Plate Depth Single Pole 9mm

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Colour/Finish	White
Dimensions (mm)	86 x 146 x 9mm
Front Plate Depth (mm)	9mm
Fixing Centre (mm)	120.6mm
Minimum Box Depth (mm)	25mm
Electrical	
Rated Operating Voltage (v)	250v
Terminal Capacity (mm ²)	3 x 2.5mmÃ,²
Number Earth Terminals	2
Rated Load Capacity (Amps)	13A
Frequency (Hz)	50/60Hz
Number Poles	2 (Double)
Kite Mark / ASTA	ASTA (lic. 913)
Performance Data	
Outlets (1 / 2) etc	2 Gang
Switch (1 / 2) etc	2 Switch
Construction	
Body Material	Urea Formaldehyde
Weight (g)	167g
Warranty Period (Years)	25
Other	



