

Model. SDB

Smoke Detector Battery Operated (Kitemark) Photoelectric

Features & Benefits

- Operated with a single 9v DC battery
- Photoelectric sensing technology
- Test button verifies battery and alarm operation
- Sleek low-profile housing design
- Low-battery warning
- Easy installation and maintenance
- Smoke Sensitivity: 3.0-6.0% Obs/m

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	Bright White
Dimensions (mm)	Ø107x35 mm
Electrical	
Power Source	9V Carbon Zinc/Alkaline/Lithium Battery
Operational Current	30mA max
Operating Temperature	0°C - 50°C
Alarm Sound Level	>85dB at 10 feet (3m)
Ambient Humidity	10%-90%RH, no condensation or icing
Battery Back Up	Y
Performance Data	
Specifications	BS EN 14604: 2005
Approvals/Certifications	CE, RoHS
Construction	
Body Material	Plastic
Weight (g)	198g
Warranty Period (Years)	3yrs
Others	
Applications	Domestic, commercial applications

