





Double Pole RCD for Consumer Units - 80A, 30mA



- Provides earth fault safety protection and prevent fatal electric shock on a person
- Protect plant & machinery from fire by a current passing from live to earth that a fuse or circuit break may
- Tunnel terminal type

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
 Do not dispose of decommissioned fitting in household waste
 Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	Grey
Electrical	
Rated Voltage (V)	230 - 240V
Frequency (Hz)	50/60Hz
Sensitivity (mA)	30mA
Terminal Capacity (mm²)	Up to 35mm ²
Performance Data	
Specification	BSEN61008-1
Max continuous voltage	80Amp
Poles	Double Poles
Туре	AC
Breaking Capacity	6kA
Approvals/Certifications	RoHS, CE
Construction	
Weight (g)	0.210Kg
Warranty Period (Years)	1Yr
Body Material	Acrylic
Others	
Applications	Domestic and commercial applications



Email. info@cedelectrical.co.uk - Website. http://www.cedelectrical.co.uk