AIRMASTER





Model. PH2TIM/LCDN

Panel Heater 2kW Digital LCD Control c/w Electronic Timer & Stat

Features & Benefits

- Lot 20 compliant
- Slim, compact and light design in corrosion resistant powder coated body.
- Highly efficient sheathed heating element with aluminium diffuser
- Easy to install using wall mounting bracket (pre-fitted)
- LCD digital control with adjustable thermostat & 24Hr/7Day programmable timer moulded at rear on side
- Silent operation with instant, even flow of heat and overheat thermal safety protection cutout

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

| rediffical opedifications | |
|----------------------------|--|
| General Information | |
| Product Colour/Finish | White |
| Dimensions (mm) | (W)940 x (H)400 x (D)85mm |
| Ingress Protection (IP) | IP24 |
| Electrical | |
| Input Voltage (v) | 220-240VAC |
| Output Rating (W) | 2000W |
| Frequency (Hz) | 50~60Hz |
| Mounting Position | Wall only |
| Mounting Bracket (Y/N) | N |
| Cable Length (Mtrs) | 1.5m, with ferrules on the ends of the cable |
| Approvals/Certifications | CE, UKCA, LOT20 |
| Performance Data | |
| Tip-Over Sensor (Y/N) | N |
| Over-Heat protection (Y/N) | Υ |
| Construction | |
| Grill | Square/Slotted |
| Nett Weight (g) | 7.2Kg |
| Gross Weight (g) | 8.5Kg |
| Warranty Period (Years) | 1Yr |
| Other | |
| Applications | Suitable for use within commercial and residential installations |
| | |

