

Model. XF4S

4" Extractor Fan Standard (FE4S)

Features & Benefits

- Class II (double insulated)
- Air movement: 80 cubic Mtrs/hr
- Rated: 48.6(dB)
- Power consumption: 20W (max)
- Complete with comprehensive installation instructions
- Suitable for the ventilation of toilets and bathrooms in accordance with IEE & Building regulations

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	White
Dimensions (mm)	164 x 154 x 88
Ingress Protection (IP)	IPX4
Cut-Hole Ø (mm)	105
Electrical	
Power Consumption	17W
Input Voltage (v)	220-240V
Frequency (Hz)	50Hz
Class	II
Approvals/Certifications	BS EN60335-1: 2012,CE, GS approved
Performance Data	
Timer	No Timer
Suitable mounting position	Wall
Air Volume/Velocity (cbm)	80
Noise level (dB)	48.6(dB)
Working temperature (°C)	0-40°C
Exhaust Outlet (Ø x mm)	Ø105mm
Construction	
Body Material	Plastic
Grill	Plastic
Weight (g)	495
Warranty Period (Years)	1
Other	
Applications	Suitable for the ventilation of toilets and bathrooms in accordance with IEE & Building regulations