

Model. ABOX60

Moulded PVC Box IP65



Features & Benefits

- IP65 VDE Approved (IP54 when used with Male Adaptors)
- Easy cable feed through high level terminals
- Comes with stainless steel V2A cover screws and blanking plug M25, seal range 9 - 18.5 mm
- Isolate protection according to VDE 0106
- Comes with high-set screw terminal, 5-pole - 6 mm² (4 x 2.5² / 4 x 4² / 3 x 6²)
- Ample wiring space and rugged construction for quick installation with the use of membrane entry

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	Grey
Dimensions (mm)	110x110x67mm
Body Material	PVC
Sealable (Y/N)	Y
Weatherproof (Y/N)	Y
Class	II
Knockouts	9xM20 or 9xM25
Specifications	EN 60529 / DIN VDE 0470-1
Approvals/Certifications	VDE, CE
Weight (g)	1.2Kg
Warranty Period (Years)	1Yr
Electrical	
Ingress Protection (IP)	IP65
Rated Cross Section (mm)	6mm ²
Rated insulation voltage AC:	690V
Environmental Attributes	
Ambient Temperature (°C)	-25 °C - 40 °C
Rel. humidity	50% - 95%
Others	
Applications	Domestic, commercial applications