

Model. ABOX160

IP65 moulded PVC Box



Features & Benefits

- IP65 VDE Approved (IP54 when used with Male Adaptors)
- Easy cable feed through high level terminals
- Comes with stainless steel V2A cover screws and blanking plug M25, seal range 9 - 18.5 mm
- Isolate protection according to VDE 0106
- Comes with high-set screw terminal, 5-pole - 16mm² (4 x 2.5mm² / 4 x 4mm² / 3 x 6mm²)
- Ample wiring space and rugged construction for quick installation with the use of membrane entry

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information

Product Colour/Finish	Grey
Dimensions (mm)	180x180x91mm
Body Material	PVC
Sealable (Y/N)	Y
Weatherproof (Y/N)	Y
Class	II
Knockouts	2xM20 3xM25/32 5xM32/M40
Specifications	EN 60529 / DIN VDE 0470-1
Approvals/Certifications	VDE, CE
Weight (g)	1.59kg
Warranty Period (Years)	1Yr

Electrical

Ingress Protection (IP)	IP65
Rated Cross Section (mm)	16mm ²
Rated insulation voltage AC:	690V

Environmental Attributes

Ambient Temperature (°C)	-25 °C - 40 °C
Rel. humidity	50% - 95%

Others

Applications	Domestic, commercial applications
--------------	-----------------------------------