

Model. CMP100

100W Rectangular Diecast Body

Features & Benefits

- Made to BS60598-2
- Gasket - Silicon rubber fits between body and visor
- Fitted with magnetic ballast (Energy Saving only)
- 20mm knockouts provided at base and both ends
- 2xPL9 Energy saving light (lamp not included)

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	Grey
Dimensions (mm)	240x115x100mm
Ingress Protection (IP)	IP65
Electrical	
Input Voltage (v)	240v
Frequency (Hz)	50hz
Wattage (W)	100w
Wattage Equivalent (W)	400W
Dimmable (Y/N)	N
Approvals/Certifications	CE/ BS-EN60598-2
Class	I
Performance Data	
Power Factor	>80
Average Lifespan (Hours)	35,000Hrs
CRI: Ra	>80
Beam Angle (°)	120°
Energy Rating (ErP)	A
Sensor	
Emergency	
Construction	
Body Material	Polycarbonate & Diecast Metal base
Diffuser Material	Polycarbonate prismatic diffuser which withstands temperatures up to 115C
Weight (g)	1.28kg
Warranty Period (Years)	1Yr
Other	
Applications	Offices/ Commercial Building/ Hospitals/ Garages/ Indoor & Outdoor

LIGHTING DESIGN

IMPORTANT!

We now offer a full lighting design service exclusively to all our customers

COMPLETELY FREE