

Model. PCMINI

Mini Photocell - Thermal Switching 16mm head

Features & Benefits

- Dust and low pressure water tight
- Dusk to dawn procedure with Thermal Photodiode

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	Black
Dimensions (mm)	40x51x26mm
Ingress Protection (IP)	IP65
Electrical	
Wattage (W)	2000W
Frequency (Hz)	50/60Hz
Power source	Mains 220-240v
Ambient Light	40° to 70°
Detection Range	Min 20lux, max. 80lux
Installation Height	17mm
Performance Data	
Specifications	BSEN60730-1
Approvals/Certifications	CE, RoHS
Construction	
Body Material	Enclosure and lens made from polycarbonate
Warranty Period (Years)	1Yr
Others	
Applications	Domestic and commercial applications

LIGHTING DESIGN

IMPORTANT!

We now offer a full lighting design service exclusively to all our customers

COMPLETELY FREE



**CED
ELECTRICAL
GROUP**

CED ELECTRICAL GROUP

44-48 Freshwater Road, Dagenham, Essex RM8 1RX

Telephone. 020 8503 8500 - Fax. 020 8503 8900

Email. info@cedelectrical.co.uk - Website. <http://www.cedelectrical.co.uk>

