

Model. PNL6636WF

36W LED Panel Fitting



Features & Benefits

- LED edge light for even light distribution with up to 80% energy saving.
- White perimeter housing to ensure seamless integration into existing decor
- Impact resistant Acrylic cover sheet for strength and durability
- White Lockable DC connector (female to driver 20cm, male to panel 30cm)

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	White
Dimensions (mm)	595x595x10mm
Cut-Hole Ø (mm)	n/a
Ingress Protection (IP)	IP20
Electrical	
Input Voltage (v)	220-240V AC
Frequency (Hz)	50/60Hz
Wattage (W)	36W
Wattage Equivalent (W)	320W
Dimmable (Y/N)	N
Approvals/Certifications	CE / EMC / RoHS
Class	II
Performance Data	
Useful Lumen Output	3000Lm
Lumens (Per Watt)	85Lm/w
Power Factor	>0.9
Average Lifespan (Hours)	35,000hrs
CRI: Ra	>80
Colour Temperature (K)	6500K
Beam Angle (°)	120°
LED Type	(Chip) Epistar SMD 4014
Number of LED (pcs)	180pcs
Energy Rating (ErP)	A+
Sensor	
Sensor Interval (mins)	n/a
Sensor Range (Mtrs / °)	n/a
Emergency	
Construction	
Body Material	Aluminium
Diffuser Material	Impact resistant Opal Diffuser
Weight (g)	2.5Kg
Warranty Period (Years)	2yrs
Other	
Applications	Suitable for normal office application

LIGHTING DESIGN

IMPORTANT!

We now offer a full lighting design service exclusively to all our customers

COMPLETELY FREE