

Model. SDL6/NW

6w 120x19mm Led Slim Downlight 330lm Whi 4000k

Features & Benefits

- Ultra slim profile recessed fittings
- Up to 80% energy saving compared to PL lamp downlighters.
- New flat panel design with instant on, no flicker or hum

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	White
Dimensions (mm)	Ø120x19mm
Cut-Hole Ø (mm)	Ø105mm
Ingress Protection (IP)	IP20
Electrical	
Input Voltage (v)	220-240V AC
Frequency (Hz)	50/60Hz
Wattage (W)	6W
Wattage Equivalent (W)	40W
Dimmable (Y/N)	N
Approvals/Certifications	CE, ROHS
Class	II
Performance Data	
Useful Lumen Output	330LM
Lumens (Per Watt)	55LM
Power Factor	>0.9
Average Lifespan (Hours)	35,000hrs
CRI: Ra	>80
Colour Temperature (K)	4000K (White)
Beam Angle (°)	120°
LED Type	SMD2835
Number of LED (pcs)	30
Energy Rating (ErP)	A
Sensor	
Sensor Interval (mins)	n/a
Sensor Range (Mtrs / °)	n/a
Emergency	
Emergency Output (W)	n/a
Emergency Period (Hours)	n/a
Construction	
Body Material	White die-cast heavy duty Aluminium body
Diffuser Material	PS
Weight (g)	0.18Kg
Warranty Period (Years)	2yrs
Other	
Applications	Indoor use eg. offices, hotels, hospitals, supermarkets, residential & public buildings

LIGHTING DESIGN

IMPORTANT!

We now offer a full lighting design service exclusively to all our customers

COMPLETELY FREE