

Model. BF455T

4' 55W Twin - Steel Body Batten Fitting with Tridonic Driver PC Diffuser & Aluminium Heat Sink

Features & Benefits

- Strip retention along full length of fitting
- LED mounting on heat sink plate for quick heat dissipation
- 20mm knockout at end cap for through wiring
- Available in:- Standard, Emergency, Motion Sensor, Emergency Motion Sensor & TCP (10%) light

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	White
Dimensions (mm)	1168x62x74mm
Ingress Protection (IP)	IP20
Electrical	
Input Voltage (v)	230V
Frequency (Hz)	50/60Hz
Wattage (W)	40W
Dimmable (Y/N)	N
Approvals/Certifications	CE
Class	I
Inrush Current (mA)	185
Performance Data	
Useful Lumen Output	4000Lm
Lumens (Per Watt)	120Lm/w
Power Factor	>0.9
Average Lifespan (Hours)	35,000k
CRI: Ra	>80
Colour Temperature (K)	4200k
Beam Angle (°)	120°
LED Type	5630
Number of LED (pcs)	76pcs
Energy Rating (ErP)	>A
Sensor	
Emergency	
Construction	
Body Material	Steel
Diffuser Material	PC
Weight (g)	1.48Kg
Warranty Period (Years)	5Yrs
Other	
Applications	Domestic and commercial applications

LIGHTING DESIGN

IMPORTANT!

We now offer a full lighting design service exclusively to all our customers

COMPLETELY FREE