

Model. AC425LED

4' 25W Single (1x25W)

Features & Benefits

- LED anti-corrosive tubeless fittings
- Mounted direct on wall or suspended by chains
- Made to BS EN 60309-2
- Optional meta clips available for extra security construction
- None replaceable LED Module with built-in SMD strip on tray.

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	Grey
Dimensions (mm)	1274x90x90mm
Ingress Protection (IP)	IP65
Electrical	
Input Voltage (v)	220-240V AC
Frequency (Hz)	50/60Hz
Wattage (W)	25W
Wattage Equivalent (W)	100W
Dimmable (Y/N)	N
Approvals/Certifications	CE, GS, EMC, RoHS, UL
Performance Data	
Useful Lumen Output	2400Lm
Lumens (Per Watt)	96Lm/w
Power Factor	>0.9
Average Lifespan (Hours)	30,000
CRI: Ra	>80
Colour Temperature (K)	6500k
Beam Angle (°)	120°
LED Type	SMD-5630
Number of LED (pcs)	52pcs
Energy Rating (ErP)	A+
Sensor	
Emergency	
Construction	
Body Material	Poly-carbonate
Diffuser Material	Dedicated 4ft. Opal Diffuser
Weight (g)	1.92Kg
Warranty Period (Years)	3Yrs
Other	
Applications	Domestic and commercial applications

LIGHTING DESIGN

IMPORTANT!

We now offer a full lighting design service exclusively to all our customers

COMPLETELY FREE