



Model. ACFL10

10W AC IP65 0.3Mtrs Cable Slim Standard Black Flood

Features & Benefits

- No driver needed in fitting - less wear out over time.
- High specification heat sink to withstand high temperatures and heat of the LED
- Surface mounted with brackets
- No pollution, no thermal radiation, Lead & Mercury free

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	White/black
Dimensions (mm)	130x90x34mm
Ingress Protection (IP)	IP65
Electrical	
Input Voltage (v)	220-240V
Frequency (Hz)	50Hz
Wattage (W)	10W
Wattage Equivalent (W)	50W
Dimmable (Y/N)	N
Approvals/Certifications	CE/ROHS
Class	I
Performance Data	
Useful Lumen Output	800Lm
Lumens (Per Watt)	80Lm/w
Power Factor	>0.9
Average Lifespan (Hours)	30,000Hrs
CRI: Ra	>65
Colour Temperature (K)	6500k
Beam Angle (°)	120°
LED Type	COB
Number of LED (pcs)	1
Energy Rating (ErP)	A+
Sensor	
Sensor Range (Mtrs / °)	
Emergency Construction	
Body Material	Aluminium
Diffuser Material	Clear tempered glass lens
Weight (g)	0.36kgs
Warranty Period (Years)	2Yrs
Other	
Applications	Parks, Accent Lighting, Billboards, Outside Wall Uplights, Gardens and Displays

LIGHTING DESIGN

IMPORTANT!

We now offer a full lighting design service exclusively to all our customers

COMPLETELY FREE