



Model. ACFL20

20W AC IP65 0.3Mtrs Cable Slim Standard Black Flood

Features & Benefits

- No driver needed in fitting - less wear out over time.
- High specification heat sink to withstand high temperatures and heat of the LED
- Surface mounted with brackets
- No pollution, no thermal radiation, Lead & Mercury free

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information

Product Colour/Finish	White
Dimensions (mm)	180x126x36mm
Ingress Protection (IP)	IP65

Electrical

Input Voltage (v)	220-240V
Frequency (Hz)	50Hz
Wattage (W)	20W
Wattage Equivalent (W)	100W
Dimmable (Y/N)	N
Approvals/Certifications	CE/ROHS
Class	I

Performance Data

Useful Lumen Output	1700Lm
Lumens (Per Watt)	85Lm/w
Power Factor	>0.9
Average Lifespan (Hours)	30000Hrs
CRI: Ra	>65
Colour Temperature (K)	6500K
Beam Angle (°)	120°
LED Type	COB
Number of LED (pcs)	1
Energy Rating (ErP)	A+

Sensor

Sensor Range (Mtrs / °)

Emergency

Construction

Body Material	Aluminium
Diffuser Material	Clear tempered glass lens
Weight (g)	0.36kgs
Warranty Period (Years)	2Yrs

Other

Applications	Parks; Accent Lighting; Billboards; Outside Wall Uplights; Gardens ; Displays
--------------	---

LIGHTING DESIGN

IMPORTANT!

We now offer a full lighting design service exclusively to all our customers

COMPLETELY FREE



CED
ELECTRICAL
GROUP

CED ELECTRICAL GROUP

44-48 Freshwater Road, Dagenham, Essex RM8 1RX

Telephone. 020 8503 8500 - Fax. 020 8503 8900

Email. info@cedelectrical.co.uk - Website. <http://www.cedelectrical.co.uk>

