

Model. FFSMD5CW

5W GU10 SMD Plastic Full Face 6500k



Features & Benefits

- Instant light without flickering, mercury free and no UV output
- Polycarbonate fire resistant cover and GU10 Lamp Base
- Up to 80% energy saving, longer life and more eco-friendly
- Non dimmable and also available in 3000K and 3W
- Fitted with a lightweight thermal plastic shell that dissipates heat more effectively

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	White
Dimensions (mm)	Ø50x54mm
Ingress Protection (IP)	IP20
Electrical	
Input Voltage (v)	220-240V
Frequency (Hz)	50/60Hz
Wattage (W)	4.5W
Wattage Equivalent (W)	50W
Dimmable (Y/N)	N
Approvals/Certifications	CE / ERP
Class	I
Performance Data	
Useful Lumen Output	345l
Lumens (Per Watt)	76
Power Factor	>0.5
Average Lifespan (Hours)	25,000Hrs
CRI: Ra	>80
Colour Temperature (K)	6500K
Beam Angle (°)	38°
LED Type	SMD
Energy Rating (ErP)	F
No. Switches (max.)	15000
Sensor	
Emergency	
Construction	
Body Material	Plastic
Diffuser Material	Plastic prismatic
Weight (g)	46
Warranty Period (Years)	2yrs
Working temperature (°C)	-25°C - +40°C
Other	
Applications	Domestic and commercial applications

LIGHTING DESIGN

IMPORTANT!

We now offer a full lighting design service exclusively to all our customers

COMPLETELY FREE



CED
ELECTRICAL
GROUP

CED ELECTRICAL GROUP

44-48 Freshwater Road, Dagenham, Essex RM8 1RX

Telephone. 020 8503 8500 - Fax. 020 8503 8900

Email. info@cedelectrical.co.uk - Website. <http://www.cedelectrical.co.uk>

