



Model. RCTS5

5 Gang Extension Lead 13Amp with Remote Control

Features & Benefits

- Overload and surge protection with reduced risk of fire and protects appliances
- Conforms to BS1363/A and BS5733/A
- Socket outlets will remain OFF after power cut, saving energy
- Power for transmitter: 12v DC (23A 1pc battery)
- Transmitter frequency: 433.92MHz with a remote control distance of 30mtrs (free area)
- Voltage: 230V~/50Hz, Max. 2400W / 120V~/60Hz, Max. 1200W

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	White
Dimensions (mm)	390 x 68 x 35mm
Ingress Protection (IP)	IP20
Electrical	
Rated Voltage (V)	240V
Rated Operating Current (Amps)	10A
Frequency (Hz)	50/60Hz
Approvals/Certifications	CE, GS, BS1363/A & BS5733/A
Performance Data	
Number of Sockets	5 Gang (max load. 2400W)
Switch Type	Unswitched
Cable Length (Mtrs)	2Mtrs
Neon (Y/N)	N
Anti-Surge (Y/N)	Y
Construction	
Body Material	Plastic
Weight (g)	600g
Warranty Period (Years)	1Yr
Other	
Applications	For use with most domestic appliances