



Model. MSLRRM44CB

14 ways Metal Consumer Unit with 100A 2P Isolator and 63A 30mA 2P RCD 2pcs + MCBs SP 2XB6/1xB16/2xB32/1xB40 4+4

Features & Benefits

- 8 way 4+4 main switch board
- New modern user friendly design quick and easy to install.
- Full metal steel casement construction for safety and to impede fire entry.
- Steel drop down solid cover to protect against dust and retard fire entry.
- Separate earth and neutral terminal at the top for easy wiring and identification.
- Generous internal cabling space above RCBO's (for time saving wiring).
- Easy knockouts all round for trucking entry and wall mounting.
- Compact and robust construction.
- Large size keyholes for easy mounting.
- Large terminals.
- None combustible cover blanks.

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	White
Dimensions (mm)	37.9x23.7x11cm
Ingress Protection (IP)	IP20
Electrical	
Rated Voltage	230 - 240V
Frequency (Hz)	50Hz
Sensitivity (mA)	30mA
Terminal Capacity (mm ²)	n/a
Performance Data	
Specifications	Board-BSEN61439-3 MCB-IEC60898 RCD-IEC61008
Isolator	100A DP
RCD	2x63A DP 30mA
Filled with MCB	2x32A, 1x16A, 2x6A, 1x40A
Approvals/Certifications	RoHS, CE
Construction	
Weight (g)	3.525Kg
Warranty Period (Years)	1yr
Body Material	Metal Clad
Knockouts	32-20-20-25-32
Number of ways	14
Number of free ways	2
Other	
Applications	Domestic, commercial applications