





## Model. AXMS42

10A Switch 4 Gang / 2 Way - ASTA

## Features & Benefits

- 10Amp (X rated) suitable for inductive load
- Supplied with M3.5 x 25mm fixing screws
- Minimum Depth Metal/Plastic/PVC Box 16mm
- Terminal Capacity 3x1.5mmÃ,²
- Three Pole Isolators provide isolation of fans for maintenance or repair without isolation of complete circuit

## Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
  Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

## **Technical Specifications**

General Information	
Colour/Finish	White
Dimensions (mm)	86 x 146 x 9mm
Front Plate Depth (mm)	9mm
Fixing Centre (mm)	120.6mm
Minimum Box Depth (mm)	16mm
Electrical	
Rated Operating Voltage (v)	240v
Terminal Capacity (mm²)	3x1.5mm²
Rated Load Capacity (Amps)	10A
Frequency (Hz)	50/60Hz
Kite Mark / ASTA	ASTA
Performance Data	
Switch (1 / 2) etc	4 Gang
Control (1 / 2 Way)	2 Way
Construction	
Body Material	Urea Formaldehyde
Warranty Period (Years)	25
Other	



Email. info@cedelectrical.co.uk - Website. http://www.cedelectrical.co.uk