





Model. AXMSINT

10A Switch Intermediate - ASTA

Features & Benefits

- 10Amp (X rated) suitable for inductive load
- Supplied with M3.5 x 25mm fixing screws
- Minimum Depth Metal/Plastic/PVC Box 16mm
- Terminal Capacity 3x1.5mmÃ,²
- Three Pole Isolators provide isolation of fans for maintenance or repair without isolation of complete circuit

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
 Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

| General Information | |
|-----------------------------|-------------------|
| Colour/Finish | White |
| Dimensions (mm) | 86 x 86 x 9mm |
| Front Plate Depth (mm) | 9mm |
| Fixing Centre (mm) | 60.3mm |
| Minimum Box Depth (mm) | 16mm |
| Electrical | |
| Rated Operating Voltage (v) | 240v |
| Terminal Capacity (mm²) | 3x1.5mm² |
| Rated Load Capacity (Amps) | 10A |
| Frequency (Hz) | 50/60Hz |
| Kite Mark / ASTA | ASTA |
| Performance Data | |
| Switch (1 / 2) etc | 1 Gang |
| Construction | |
| Body Material | Urea Formaldehyde |
| Warranty Period (Years) | 25 |
| Other | |

