



Model. AXMSARC

10A Architrave Switch 1 Gang 2 Way

Features & Benefits

- 10Amp (X rated) suitable for inductive load
- Supplied with M3.5 x 25mm fixing screws
- Minimum Depth - Metal/Plastic/PVC Box 16mm
- Terminal Capacity - 3x1.5mm²
- Three Pole Isolators provide isolation of fans for maintenance or repair without isolation of complete circuit

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Product Summary

The Axiom Vertex range of Wiring Accessories. Designed specifically with both the contractor and wholesaler in mind. Manufactured in accordance to International standards such as ASTA, CE, and RoHS. They fulfil all the requirements in terms of safety and performance to meet EU and British standards for safety against electric shock. Offering outstanding value whilst ensuring they meet all relevant safety standards.

Technical Specifications

General Information	
Colour/Finish	White
Dimensions (mm)	86 x 32 x 9mm
Front Plate Depth (mm)	9mm
Fixing Centre (mm)	60.3mm (vertical)
Minimum Box Depth (mm)	16mm
Ingress Protection (IP)	n/a
Electrical	
Rated Operating Voltage (v)	240v
Terminal Capacity (mm ²)	3x1.5mm ²
Cable Clamp Capacity (mm)	n/a
Number Earth Terminals	n/a
Rated Load Capacity (Amps)	10A
Frequency (Hz)	50/60Hz
Number Poles	n/a
Conductor Size (mm ²)	n/a
Approvals	n/a
Kite Mark / ASTA	n/a
Minimum Load	n/a
Maximum Load	n/a
Performance Data	
Outlets (1 / 2) etc	n/a
Switch (1 / 2) etc	1 Gang
Control (1 / 2 Way)	2 Way
Lugs	n/a
Knockouts	n/a
Flex Inlet	n/a
Construction	
Body	Urea Formaldehyde
Insert Colour	n/a
Weight	n/a
Warranty (Years)	25
Other	
Applications	n/a