

## Model. AXMSK1

1 Gang Unswitched Socket 13A



### Features & Benefits

- Contact Gap - 3mm
- Minimum Depth - Plastic/PVC box - 25mm
- Terminal Capacity - 4x2.5mm<sup>2</sup> (13Amp only)
- 1 Earth Terminals for easy installation - Single Pole
- Supplied with M3.5 x 30mm fixing screws
- Front Plate Depth - Single Pole - 9mm

### Safety Information

**IMPORTANT** - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

### Product Summary

The Axiom Vertex range of Wiring Accessories. Designed specifically with both the contractor and wholesaler in mind. Manufactured in accordance to International standards such as ASTA, CE, and RoHS. They fulfil all the requirements in terms of safety and performance to meet EU and British standards for safety against electric shock. Offering outstanding value whilst ensuring they meet all relevant safety standards.

### Technical Specifications

| General Information                  |                        |
|--------------------------------------|------------------------|
| Colour/Finish                        | White                  |
| Dimensions (mm)                      | 86 x 86 x 9mm          |
| Front Plate Depth (mm)               | 9mm                    |
| Fixing Centre (mm)                   | 60.3mm                 |
| Minimum Box Depth (mm)               | 25mm                   |
| Ingress Protection (IP)              | n/a                    |
| Electrical                           |                        |
| Rated Operating Voltage (v)          | 250v                   |
| Terminal Capacity (mm <sup>2</sup> ) | 3 x 2.5mm <sup>2</sup> |
| Cable Clamp Capacity (mm)            | n/a                    |
| Number Earth Terminals               | 1                      |
| Rated Load Capacity (Amps)           | 13A                    |
| Frequency (Hz)                       | 50Hz                   |
| Number Poles                         | 1 (Single)             |
| Conductor Size (mm <sup>2</sup> )    | n/a                    |
| Approvals                            | n/a                    |
| Kite Mark / ASTA                     | ASTA (lic.914)         |
| Minimum Load                         | n/a                    |
| Maximum Load                         | n/a                    |
| Performance Data                     |                        |
| Outlets (1 / 2) etc                  | 1 Gang                 |
| Switch (1 / 2) etc                   | n/a                    |
| Control (1 / 2 Way)                  | n/a                    |
| Lugs                                 | n/a                    |
| Knockouts                            | n/a                    |
| Flex Inlet                           | n/a                    |
| Construction                         |                        |
| Body                                 | Urea Formaldehyde      |
| Insert Colour                        | n/a                    |
| Weight                               | 90g                    |
| Warranty (Years)                     | 25                     |
| Other                                |                        |
| Applications                         | n/a                    |