





2 Gang Unswitched Socket 13A

Features & Benefits

- Contact Gap 3mm
- Minimum Depth Plastic/PVC box 25mm
- Terminal Capacity 4x2.5mmÃ,² (13Amp only)
- Single Pole
- Supplied with M3.5 x 30mm fixing screws
- Front Plate Depth Single Pole 9mm

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
 Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Colour/Finish	White
Dimensions (mm)	86 x 146 x 9mm
Front Plate Depth (mm)	9mm
Fixing Centre (mm)	120.6mm
Minimum Box Depth (mm)	25mm
Electrical	
Rated Operating Voltage (v)	250v
Terminal Capacity (mm²)	3 x 2.5mmÃ,²
Number Earth Terminals	1
Rated Load Capacity (Amps)	13A
Frequency (Hz)	50Hz
Number Poles	1 (Single)
Kite Mark / ASTA	ASTA (lic. 913)
Performance Data	
Outlets (1 / 2) etc	2 Gang
Construction	
Body Material	Urea Formaldehyde
Weight (g)	131g
Warranty Period (Years)	25
Other	

