

## Model. AXMSSK1/USB

1 Gang Switched Socket c/w USB



### Features & Benefits

There are currently no features entered for this product item.

### Safety Information

**IMPORTANT** - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

### Product Summary

Axiom Vertex single switched USB Charger sockets have a key competitive advantage in terms of their two 5v USB sockets. One has a rating of 1.2A - primarily for mobile phones, whilst the second has a 2.4A rating for charging iPads and tablets. As a result, virtually all modern IT devices can be charged quickly from one mains socket. Products comply with BS standards 5733 and 1363.

### Technical Specifications

| General Information                  |                        |
|--------------------------------------|------------------------|
| Colour/Finish                        | White                  |
| Dimensions (mm)                      | 86 x 86 x 9mm          |
| Front Plate Depth (mm)               | 9mm                    |
| Fixing Centre (mm)                   | 60.3mm                 |
| Minimum Box Depth (mm)               | 25mm                   |
| Ingress Protection (IP)              | n/a                    |
| Electrical                           |                        |
| Rated Operating Voltage (v)          | 250v                   |
| Terminal Capacity (mm <sup>2</sup> ) | 3 x 2.5mm <sup>2</sup> |
| Cable Clamp Capacity (mm)            | n/a                    |
| Number Earth Terminals               | 1 (single)             |
| Rated Load Capacity (Amps)           | 13A                    |
| Frequency (Hz)                       | 50/60Hz                |
| Number Poles                         | n/a                    |
| Conductor Size (mm <sup>2</sup> )    | n/a                    |
| Approvals                            | n/a                    |
| Kite Mark / ASTA                     | n/a                    |
| Minimum Load                         | n/a                    |
| Maximum Load                         | n/a                    |
| Performance Data                     |                        |
| Outlets (1 / 2) etc                  | 1 Gang                 |
| Switch (1 / 2) etc                   | 1                      |
| Control (1 / 2 Way)                  | n/a                    |
| Lugs                                 | n/a                    |
| Knockouts                            | n/a                    |
| Flex Inlet                           | n/a                    |
| Construction                         |                        |
| Body                                 | Urea Formaldehyde      |
| Insert Colour                        | n/a                    |
| Weight                               | 68g                    |
| Warranty (Years)                     | 25                     |
| Other                                |                        |
| Applications                         | n/a                    |