



## Model. AXMS22

2 Gang 2 Way Switch

### Features & Benefits

- 10Amp (X rated) suitable for inductive load
- Supplied with M3.5 x 25mm fixing screws
- Minimum Depth - Metal/Plastic/PVC Box 16mm
- Terminal Capacity - 3x1.5mm<sup>2</sup>

### Safety Information

**IMPORTANT** - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

### Product Summary

The Axiom Vertex Range of white accessories, whilst retaining Axiom quality, is a compact economy range of key products used by contractors on a daily basis, but priced to meet the competitive needs of this sector. In switches there are 1, 2, 3 and 4 gang, intermediate and fan 10A switches, plus 20A DP and 45A DP cooker and ceiling switches. Sockets comprise 13A single and twin switched sockets, including a twin USB charger version. 13A switched and un-switched connection units, 10A 6" pendants plus 1 & 2 gang dry lining boxes complete the range, all of which are fully ASTA approved.

### Technical Specifications

General Information	
Colour/Finish	White
Dimensions (mm)	86 x 86 x 9mm
Front Plate Depth (mm)	9mm
Fixing Centre (mm)	60.3mm
Minimum Box Depth (mm)	16mm
Ingress Protection (IP)	n/a
Electrical	
Rated Operating Voltage (v)	n/a
Terminal Capacity (mm <sup>2</sup> )	3 x 1.5mm <sup>2</sup>
Cable Clamp Capacity (mm)	n/a
Number Earth Terminals	n/a
Rated Load Capacity (Amps)	10A
Frequency (Hz)	50/60Hz
Number Poles	1
Conductor Size (mm <sup>2</sup> )	n/a
Approvals	n/a
Kite Mark / ASTA	ASTA
Minimum Load	n/a
Maximum Load	n/a
Performance Data	
Outlets (1 / 2) etc	n/a
Switch (1 / 2) etc	2 Gang
Control (1 / 2 Way)	2 Way
Lugs	n/a
Knockouts	n/a
Flex Inlet	n/a
Construction	
Body	Urea Formaldehyde
Insert Colour	n/a
Weight	85g
Warranty (Years)	25
Other	
Applications	Domestic and commercial applications