





## Model. AXMS22

2 Gang 2 Way Switch

## Features & Benefits

- 10Amp (X rated) suitable for inductive load
- Supplied with M3.5 x 25mm fixing screws
  Minimum Depth Metal/Plastic/PVC Box 16mm
  Terminal Capacity 3x1.5mmÃ,Â<sup>2</sup>

## Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
  Do not dispose of decommissioned fitting in household waste
  Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

## **Technical Specifications**

General Information	
Colour/Finish	White
Dimensions (mm)	86 x 86 x 9mm
Front Plate Depth (mm)	9mm
Fixing Centre (mm)	60.3mm
Minimum Box Depth (mm)	16mm
Electrical	
Terminal Capacity (mm <sup>2</sup> )	3 x 1.5mm <sup>2</sup>
Rated Load Capacity (Amps)	10A
Frequency (Hz)	50/60Hz
Number Poles	1
Kite Mark / ASTA	ASTA
Performance Data	
Switch (1 / 2) etc	2 Gang
Control (1 / 2 Way)	2 Way
Construction	
Body Material	Urea Formaldehyde
Weight (g)	85g
Warranty Period (Years)	25
Other	

Applications

Domestic and commercial applications

