# -AIRMASTER





# Model. IFH2H

2Kw Industrial Fan Heater

#### Features & Benefits

- Supplied complete with cord and 13A BS approved 3 pin plug
- 3 Settings (Low 25/Medium1000/High2000W) with heat resistant carrying handle
- Adjustable thermostat 65Ã,°C with overheating protection and tip over safety switch
- Sturdy and durable with rubber feet for extra stability, stainless steel heating element and silver control
  panel
- Quiet running with upto 40m3 heating area capacity, no fumes, no odours or humidity

## Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

### **Technical Specifications**

General Information           Product Colour/Finish         Red/Black           Dimensions (mm)         250X240X348mm           Ingress Protection (IP)         IPX4           Electrical         Input Voltage (V)           Input Voltage (V)         220 - 240V AC           Output Rating (W)         2kW           Frequency (Hz)         50Hz           Working temperature (°C)         65°C           Mounting Position         Floor Standing           Mounting Bracket (Y/N)         None           Cable Length (Mtrs)         Complete with Cable           Class         I           Approvals/Certifications         CE, intertek GS           Performance Data         I           Air Volume/Velocity (cbm)         186m3/h           Noise level (dB)         Quiet running           Tip-Over Sensor (Y/N)         Y           Construction         Y           Body Material         Powder coated heat-resistant steel housing with stainless steel heating element           Grill         Sturdy metal grills           Nett Weight (g)         3.5KG           Gross Weight (g)         4.0KG           Warranty Period (Years)         1Yr           Warranty Period (Years)         1Yr </th <th></th> <th></th>		
Dimensions (mm) 250X240X348mm Ingress Protection (IP) IPX4  Electrical Input Voltage (v) 220 - 240V AC Output Rating (W) 2kW Frequency (Hz) 50Hz Working temperature (°C) 65°C Mounting Position Floor Standing Mounting Bracket (Y/N) None Cable Length (Mtrs) Complete with Cable Class I Approvals/Certifications CE, intertek GS  Performance Data Air Volume/Velocity (cbm) 186m3/h Noise level (dB) Quiet running Tip-Over Sensor (Y/N) Y Construction  Body Material Powder coated heat-resistant steel housing with stainless steel heating element Grill Sturdy metal grills Nett Weight (g) 3.5KG Gross Weight (g) 4.0KG Warranty Period (Years) 1Yr Other  Applications Suitable for well insulated spaces or occasional use household,	General Information	
Ingress Protection (IP)  Electrical  Input Voltage (v)  Output Rating (W)  Frequency (Hz)  Working temperature (°C)  Mounting Position  Mounting Bracket (Y/N)  Cable Length (Mtrs)  Complete with Cable  Class  I  Approvals/Certifications  CE, intertek GS  Performance Data  Air Volume/Velocity (cbm)  Noise level (dB)  Tip-Over Sensor (Y/N)  Over-Heat protection (Y/N)  Powder coated heat-resistant steel housing with stainless steel heating element  Grill  Sturdy metal grills  Nett Weight (g)  Gross Weight (g)  Warranty Period (Years)  Applications  Suitable for well insulated spaces or occasional use household,	Product Colour/Finish	Red/Black
Electrical Input Voltage (v) 220 - 240V AC Output Rating (W) 2kW Frequency (Hz) 50Hz Working temperature (°C) 65°C Mounting Position Floor Standing Mounting Bracket (Y/N) None Cable Length (Mtrs) Complete with Cable Class I Approvals/Certifications CE, intertek GS Performance Data Air Volume/Velocity (cbm) 186m3/h Noise level (dB) Quiet running Tip-Over Sensor (Y/N) Y Construction  Body Material Powder coated heat-resistant steel housing with stainless steel heating element Grill Sturdy metal grills Nett Weight (g) 3.5KG Gross Weight (g) 4.0KG Warranty Period (Years) 1Yr Warranty Period (Years) 1Yr Other  Applications Suitable for well insulated spaces or occasional use household,	Dimensions (mm)	250X240X348mm
Input Voltage (v) 220 - 240V AC Output Rating (W) 2kW Frequency (Hz) 50Hz Working temperature (°C) 65°C Mounting Position Floor Standing Mounting Bracket (Y/N) None Cable Length (Mtrs) Complete with Cable Class I Approvals/Certifications CE, intertek GS  Performance Data Air Volume/Velocity (cbm) 186m3/h Noise level (dB) Quiet running Tip-Over Sensor (Y/N) Y Over-Heat protection (Y/N) Y Construction  Body Material Powder coated heat-resistant steel housing with stainless steel heating element Grill Sturdy metal grills Nett Weight (g) 3.5KG Gross Weight (g) 4.0KG Warranty Period (Years) 1Yr Other  Applications Suitable for well insulated spaces or occasional use household,	Ingress Protection (IP)	IPX4
Output Rating (W) 2kW Frequency (Hz) 50Hz Working temperature (°C) 65°C Mounting Position Floor Standing Mounting Bracket (Y/N) None Cable Length (Mtrs) Complete with Cable Class I Approvals/Certifications CE, intertek GS  Performance Data Air Volume/Velocity (cbm) 186m3/h Noise level (dB) Quiet running Tip-Over Sensor (Y/N) Y Over-Heat protection (Y/N) Y Construction  Body Material Powder coated heat-resistant steel housing with stainless steel heating element Grill Sturdy metal grills Nett Weight (g) 3.5KG Gross Weight (g) 4.0KG Warranty Period (Years) 1Yr Warranty Period (Years) 1Yr Warranty Period (Years) Suitable for well insulated spaces or occasional use household,	Electrical	
Frequency (Hz) 50Hz  Working temperature (°C) 65°C  Mounting Position Floor Standing  Mounting Bracket (Y/N) None  Cable Length (Mtrs) Complete with Cable  Class I  Approvals/Certifications CE, intertek GS  Performance Data  Air Volume/Velocity (cbm) 186m3/h  Noise level (dB) Quiet running  Tip-Over Sensor (Y/N) Y  Construction  Body Material Powder coated heat-resistant steel housing with stainless steel heating element  Grill Sturdy metal grills  Nett Weight (g) 3.5KG  Gross Weight (g) 4.0KG  Warranty Period (Years) 1Yr  Warranty Period (Years) 1Yr  Applications  Suitable for well insulated spaces or occasional use household,	Input Voltage (v)	220 - 240V AC
Working temperature (°C)  Mounting Position Floor Standing Mounting Bracket (Y/N) Cable Length (Mtrs) Complete with Cable Class I Approvals/Certifications CE, intertek GS  Performance Data Air Volume/Velocity (cbm) Noise level (dB) Quiet running Tip-Over Sensor (Y/N) Vover-Heat protection (Y/N) Y Construction  Body Material Grill Sturdy metal grills Nett Weight (g) Gross Weight (g) Warranty Period (Years) Other  Applications  Floor Standing Ross CE, intertek GS  Quiet running Ty-Over Sensor (Y/N) Y Construction  Powder coated heat-resistant steel housing with stainless steel heating element element Sturdy metal grills 1	Output Rating (W)	2kW
Mounting Position Floor Standing Mounting Bracket (Y/N) None Cable Length (Mtrs) Complete with Cable Class I Approvals/Certifications CE, intertek GS Performance Data Air Volume/Velocity (cbm) 186m3/h Noise level (dB) Quiet running Tip-Over Sensor (Y/N) Y Over-Heat protection (Y/N) Y Construction  Body Material Powder coated heat-resistant steel housing with stainless steel heating element Grill Sturdy metal grills Nett Weight (g) 3.5KG Gross Weight (g) 4.0KG Warranty Period (Years) 1Yr Warranty Period (Years) 1Yr Other  Applications  Floor Standing None Complete with Cable CE, intertek GS  Performance Descriptions  186m3/h Y Y V V V V V V V Construction V Y Construction Suitable for well insulated spaces or occasional use household,	Frequency (Hz)	50Hz
Mounting Bracket (Y/N) None Cable Length (Mtrs) Complete with Cable Class I Approvals/Certifications CE, intertek GS  Performance Data Air Volume/Velocity (cbm) 186m3/h Noise level (dB) Quiet running Tip-Over Sensor (Y/N) Y Over-Heat protection (Y/N) Y Construction  Body Material Powder coated heat-resistant steel housing with stainless steel heating element Grill Sturdy metal grills Nett Weight (g) 3.5KG Gross Weight (g) 4.0KG Warranty Period (Years) 1Yr Warranty Period (Years) 1Yr Other  Applications  None Complete with Cable I Remaid CH, II Remaid CH, I	Working temperature (°C)	65°C
Cable Length (Mtrs) Class Class I Approvals/Certifications CE, intertek GS Performance Data Air Volume/Velocity (cbm) Noise level (dB) Quiet running Tip-Over Sensor (Y/N) Voer-Heat protection (Y/N) Y Construction  Body Material Powder coated heat-resistant steel housing with stainless steel heating element Grill Sturdy metal grills Nett Weight (g) 3.5KG Gross Weight (g) 4.0KG Warranty Period (Years) Vir Other  Suitable for well insulated spaces or occasional use household,	Mounting Position	Floor Standing
Class I Approvals/Certifications CE, intertek GS  Performance Data  Air Volume/Velocity (cbm) 186m3/h  Noise level (dB) Quiet running  Tip-Over Sensor (Y/N) Y  Over-Heat protection (Y/N) Y  Construction  Body Material Powder coated heat-resistant steel housing with stainless steel heating element  Grill Sturdy metal grills  Nett Weight (g) 3.5KG  Gross Weight (g) 4.0KG  Warranty Period (Years) 1Yr  Warranty Period (Years) 1Yr  Other  Applications  CE, intertek GS  Performance  Lead (SE)  Applications  I Som Weight (G) Suitable for well insulated spaces or occasional use household,	Mounting Bracket (Y/N)	None
Approvals/Certifications  Performance Data  Air Volume/Velocity (cbm)  Noise level (dB)  Quiet running  Tip-Over Sensor (Y/N)  Over-Heat protection (Y/N)  Powder coated heat-resistant steel housing with stainless steel heating element  Grill  Sturdy metal grills  Nett Weight (g)  Gross Weight (g)  Warranty Period (Years)  Other  Applications  CE, intertek GS  Performance  186m3/h  Quiet running  Y  Powder coated heat-resistant steel housing with stainless steel heating element  Sturdy metal grills  4.0KG  1Yr  Applications  Suitable for well insulated spaces or occasional use household,	Cable Length (Mtrs)	Complete with Cable
Performance Data  Air Volume/Velocity (cbm)  Noise level (dB)  Quiet running  Tip-Over Sensor (Y/N)  Vover-Heat protection (Y/N)  Body Material  Powder coated heat-resistant steel housing with stainless steel heating element  Grill  Sturdy metal grills  Nett Weight (g)  Gross Weight (g)  Warranty Period (Years)  Tyr  Warranty Period (Years)  Other  Suitable for well insulated spaces or occasional use household,	Class	1
Air Volume/Velocity (cbm)  Noise level (dB)  Cuiet running  Tip-Over Sensor (Y/N)  Over-Heat protection (Y/N)  Powder coated heat-resistant steel housing with stainless steel heating element  Grill  Sturdy metal grills  Nett Weight (g)  Gross Weight (g)  Warranty Period (Years)  Varranty Period (Years)  Applications  186m3/h  Quiet running  Powder coated heat-resistant steel housing with stainless steel heating element  Sturdy metal grills  3.5KG  4.0KG  Warranty Period (Years)  1Yr  Other  Suitable for well insulated spaces or occasional use household,	Approvals/Certifications	CE, intertek GS
Noise level (dB) Quiet running  Tip-Over Sensor (Y/N) Y  Over-Heat protection (Y/N) Y  Construction  Body Material Power Coated heat-resistant steel housing with stainless steel heating element  Grill Sturdy metal grills  Nett Weight (g) 3.5KG  Gross Weight (g) 4.0KG  Warranty Period (Years) 1Yr  Warranty Period (Years) 1Yr  Other  Suitable for well insulated spaces or occasional use household,	Performance Data	
Tip-Over Sensor (Y/N) Y Over-Heat protection (Y/N) Y  Construction  Body Material Powder coated heat-resistant steel housing with stainless steel heating element  Grill Sturdy metal grills Nett Weight (g) 3.5KG Gross Weight (g) 4.0KG Warranty Period (Years) 1Yr Warranty Period (Years) 1Yr Other  Applications Suitable for well insulated spaces or occasional use household,	Air Volume/Velocity (cbm)	186m3/h
Over-Heat protection (Y/N)  Construction  Body Material  Fowder coated heat-resistant steel housing with stainless steel heating element  Sturdy metal grills  Nett Weight (g)  Gross Weight (g)  4.0KG  Warranty Period (Years)  1Yr  Warranty Period (Years)  Other  Suitable for well insulated spaces or occasional use household,	Noise level (dB)	Quiet running
Construction  Body Material Powder coated heat-resistant steel housing with stainless steel heating element  Grill Sturdy metal grills  Nett Weight (g) 3.5KG  Gross Weight (g) 4.0KG  Warranty Period (Years) 1Yr  Warranty Period (Years) 1Yr  Other  Applications Suitable for well insulated spaces or occasional use household,	Tip-Over Sensor (Y/N)	Υ
Body Material Powder coated heat-resistant steel housing with stainless steel heating element  Grill Sturdy metal grills  Nett Weight (g) 3.5KG  Gross Weight (g) 4.0KG  Warranty Period (Years) 1Yr  Warranty Period (Years) 1Yr  Other  Applications Suitable for well insulated spaces or occasional use household,	Over-Heat protection (Y/N)	Υ
element  Grill Sturdy metal grills  Nett Weight (g) 3.5KG  Gross Weight (g) 4.0KG  Warranty Period (Years) 1Yr  Warranty Period (Years) 1Yr  Other  Applications Suitable for well insulated spaces or occasional use household,	Construction	
Nett Weight (g) 3.5KG Gross Weight (g) 4.0KG Warranty Period (Years) 1Yr Warranty Period (Years) 1Yr Other Suitable for well insulated spaces or occasional use household,	Body Material	
Gross Weight (g) 4.0KG Warranty Period (Years) 1Yr Warranty Period (Years) 1Yr Other  Applications Suitable for well insulated spaces or occasional use household,	Grill	Sturdy metal grills
Warranty Period (Years)  Warranty Period (Years)  1Yr  Other  Applications  Suitable for well insulated spaces or occasional use household,	Nett Weight (g)	3.5KG
Warranty Period (Years)  Other  Applications  Suitable for well insulated spaces or occasional use household,	Gross Weight (g)	4.0KG
Other  Applications  Suitable for well insulated spaces or occasional use household,	Warranty Period (Years)	1Yr
Applications Suitable for well insulated spaces or occasional use household,	Warranty Period (Years)	1Yr
Applications	Other	
	Applications	

