

Model. FPD1065WHI/QC

Fire Rated Downlighter GU10 Ip65 Quick Connector D/C S/C

Features & Benefits

- Fitted with detachable Quick Fix tool-less connector for easy installation
- All steel body with self sealing fire suppression mechanism and approved to BS476 pt21
- IP65 and resistant to fire 30, 60 & 90 minutes with full gasket seal for high moisture areas
- Fixed (non-adjustable) and suitable for GU10 LED 5W lamps

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	White Finish
Dimensions (mm)	135xØ85mm
Ingress Protection (IP)	IP65
Cut-Hole Ø (mm)	Ø72mm
Electrical	
Input Voltage (v)	230/240Vac
Frequency (Hz)	50Hz
Dimmable (Y/N)	None dimmable
Approvals/Certifications	CE approved to BS476 pt21
Performance Data	
Type (Single or Twin)	Single
Class	I
Construction	
Body Material	Black steel body with die-cast Aluminium bezel
Diffuser Material	Glass
Weight (g)	0.5Kg
Warranty Period (Years)	1Yr
Others	
Applications	Domestic and commercial applications

LIGHTING DESIGN

IMPORTANT!

We now offer a full lighting design service exclusively to all our customers

COMPLETELY FREE