





30W LED Slim curved floodlight with IP65 integrated junction box, 2400Lm, 6500K

## Features & Benefits

- Durable, slim and sleek design with integrated junction box
- Angled bracket for easy installation and flexible positioning
- Complete with 3x1.0mm2 cable and energy-saving LED luminaire
- Black powder coated die-cast aluminium body with heat dissipater and clear tempered glass



IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
  Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

## **Technical Specifications**

1	
General Information	
Product Colour/Finish	Black
Dimensions (mm)	175x125x55mm
Cut-Hole Ø (mm)	N/A
Ingress Protection (IP)	IP65
Electrical	
Input Voltage (v)	220-240V
Frequency (Hz)	50/60Hz
Wattage (W)	30W
Dimmable (Y/N)	None dimmable
Approvals/Certifications	CE-LVD, CE-EMC and RoSH
Class	
Inrush Current (mA)	135mA
Performance Data	
Useful Lumen Output	2400lm
Power Factor	>0.90
CRI: Ra	>70
Colour Temperature (K)	6500K
Beam Angle (°)	110°
LED Type	SMD2835 0.5W
Number of LED (pcs)	42pcs
Sensor	
Sensor Interval (mins)	7sec~10mins
Sensor Range (Mtrs / °)	Max. 10m
Emergency	
Construction	
Body Material	Diecast Aluminium body
Diffuser Material	Clear tempered glass
Weight (g)	430g
Warranty Period (Years)	2yrs
Warranty Period (Years)	2yrs
Other	
Applications	Architecture, parks and gardens, facades, roof top and billboard

## LIGHTING DESIGN

## **IMPORTANT!**

We now offer a full lighting design service exclusively to all our customers

COMPLETELY FREE

